

MITEL

## IP Programmable Key Modules

### Improve call handling with Programmable Key Modules for the Mitel 5220 and 5235 IP Phones



The Mitel® IP Programmable Key Modules (PKM) extend the capability of the Mitel 5220 and 5235 IP Phones with additional buttons. Ideal for receptionists, departmental administrative assistants, and people who require additional personal keys, PKMs can be easily programmed through the phone and can be used to monitor and manage multiple lines beyond the capacity of the 5220 and 5235 IP Phones.

#### Improve Call Handling

Administrative assistants can use the 12- and 48-button IP PKMs to monitor and manage multiple lines beyond the 14-line capacity of the 5220 IP Phone and the 24-line capacity of the 5235 IP Phone. The 12-button IP PKM adds 12 keys while the 48-button IP PKM adds 48 additional keys with one module, and 96 keys with two modules connected to a 5220 or 5235 IP Phone.

A IP PKM Interface Module added to the back of a 5220 or 5235 IP Phone allows the 12- and 48-button IP PKMs to easily connect to an IP phone, without the need for an additional LAN port.

When used in either an enterprise or small business environment, the IP PKMs improve call handling for both employees and customers.

#### Easily Programmed

With the PKMs, 12, 48 or 96 additional keys can be easily programmed as feature keys, speed call keys, extension keys, Direct Station Select (DSS) keys, or line appearance keys. Each key has an associated indicator light, which gives the status of that extension or programmed feature. Personal keys can be easily programmed through the IP phones themselves or the web browser-based configuration tool of the 5220 IP Phone.



it's about **YOU**

## Physical Characteristics

### IP PKM (12 Button):

Dimensions: 6.75 in. x 2.25 in (17 cm x 5.7 cm)

Weight: 0.6 lbs. (0.3 kg)

### IP PKM (48 Button)

Dimensions: 7.25 in x 9.25 in (18.4 cm x 23.5 cm)

Weight: 2.1 lbs (0.9 kg)

## Voice QoS

IEEE 802.1 p/q

## Powering Options

### 5220 IP Phone:

- Powered via the adapter power port or Powered over Ethernet with a power source compliant to IEEE 802.3af
- 24VDC power adapter or 48VDC Ethernet Power Adapter available, purchased separately (if required)

### 5235 IP Phone:

- Powered over Ethernet with a power source compliant to IEEE 802.3af
- 48VDC Ethernet Power Adapter available, purchased separately (if required)

## System Requirements:

- Mitel 3300 Integrated Communications Platform (ICP), Release 5.2 or later
- Mitel SX-200 Integrated Communications Platform (ICP), Release 2.0 or later

#### North America

(613) 592 2122  
1 800 648 3579

#### Benelux

Tel: +31 (0)30 85 00 030  
Fax: +31 (0)30 85 00 031

#### Middle East

Tel: +971 4 3916721  
Fax: +971 4 3915288

#### Latin America

(613) 592 2122  
1 800 648 3579

#### Italy

Tel: +39 02 2130231  
Fax: +39 02 21302333

#### South Africa

Tel: +27 82 559 8688  
Fax: +27 11 784 6916

#### UK

Tel: +44 (0)1291 430000  
Fax: +44 (0)1291 430400

#### Germany, Switzerland, Austria

Tel: +49 (0)211 5206480  
Fax: +49 (0)211 52064899

#### Asia-Pacific

Tel: +852 2508 9780  
Fax: +852 2508 9232

#### France

Tel: +33 (0)1 61 37 00 90  
Fax: +33 (0)1 61 37 00 99

#### Portugal and Spain

Tel: +34 91 350 66 33  
Fax: +34 91 350 70 14

[www.mitel.com](http://www.mitel.com)



THIS DOCUMENT IS PROVIDED TO YOU FOR INFORMATIONAL PURPOSES ONLY. The information furnished in this document, believed by Mitel to be accurate as of the date of its publication, is subject to change without notice. Mitel assumes no responsibility for any errors or omissions in this document and shall have no obligation to you as a result of having made this document available to you or based upon the information it contains.

M MITEL (design) is a registered trademark of Mitel Networks Corporation. All other products and services are the registered trademarks of their respective holders.

© Copyright 2005, Mitel Networks Corporation. All Rights Reserved.

GD 9649 PN 51006101RB-EN